

# CATEGORY 5E UTP PATCH PANEL

High quality Category 5e patch panels from NORDEN are color coded for both 568A and 568B standards. Dual type Termination block accept both Krone and 110 type punch down tool. Robust and installer friendly design makes reduced installation and operating costs. The pack includes cable manager, mounting screws and cable ties. Modular and expandable comprehensive product range provides up to 48 ports in a single panel.



## COMPLIANCE

IEEE 802.af, IEEE 802.3at for PoE applications.  
ISO/IEC 11801 Class E, TIA/EIA-568B.2-1

## DESIGN & MATERIALS

Panel Type	Flat
Panel Width	483 mm (19")
Panel Height	1U: 44.2 mm & 2U: 88.4 mm
Outlet Style	Unkeyed RJ-45
Outlets	24 - 48 Modular Port
Connector Module Holder	High Impact, Flame-Retardant Plastic Compound, UL 94 V-0
Cover Colour and Material	Black, Powder Coated Steel

## STANDARDS

Wiring Standards	EIA/TIA 568 A/B
Flammability rating	UL 94V-0
Transmission	ISO/IEC 11801:2002 ANSI /TIA/EIA-568.B.2-10

## ORDERING INFORMATION

Part Number	Description
121-21P18024B	Category 5e UTP Patch Panel 24 Port Unloaded
121-21P18024L	Category 5e UTP Patch Panel 24 Port Loaded
121-21P18048L	Category 5e UTP Patch Panel 48 Port Loaded

## PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
121-21P18024B	20 x 1	Carton Box	9.0	11.0	530 x 430 x 310
121-21P18024L	20 x 1	Carton Box	11.0	13.0	530 x 430 x 310
121-21P18048L	10 x 1	Carton Box	11.4	13.6	530 x 430 x 310