

FIBER OPTIC CROSS CONNECT CABINET 144 PORT

Fiber optic cross connection cabinet is an external optical equipment that is especially designed for external optical nodes in access net work.



FEATURES

- High intensity and anti-erosion performance
- Able to counter abrupt climate change and extreme environment
- Capacity can be flexibly customized as required
- Installation is quick and convenient
- Built-in direct splice unit is capable for providing direct connection function.
- Perfect design of fiber wiring routing could facilitate management and maintenance of fibers
- With secure and reliable fastening and grounding protection devices for the optic fiber
- Applicable to strap-shaped and non-strap shaped fibers

MATERIAL

SMC or Cold-roll steel

TECHNICAL PARAMETERS:

Nominal work wave-length	850nm, 1310nm, 1550nm
Protection level	IP65
Work Temperature	-45°C +85°C
Storage temperature	-100°C-+85°C
Relative humidity	≤ 85% (+30°C)
Atmospheric pressure	70~106 Kpa
Insertion loss	≤ 0.2dB
Return loss	≥ 45dB (PC), 55dB(UPC), 60dB(APC)
Isolation resistance(between frame and protection grounding)	> 1000 MΩ/500V(DC)

FIBER OPTIC CROSS CONNECT CABINET 144 PORT

ORDERING INFORMATION

Part Number	Description	Dimension (cm)
600-144LCX	Fiber Optic Cross Connect Cabinet 144 LC Port	96 x 53 x 32.5
600-144SCX	Fiber Optic Cross Connect Cabinet 144 SC Port	96 x 53 x 32.5
600-144STX	Fiber Optic Cross Connect Cabinet 144 ST Port	96 x 53 x 32.5

PACKING INFORMATION

Part Number	Fibre Quantity	Packing Mode	N.W (kg)	G.W(kg)
600-144LCX	144	Wooden Carton	40	50
600-144SCX	144	Wooden Carton	40	50
600-144STX	144	Wooden Carton	40	50