

FIBRE OPTIC SPLICE CLOSURE

FOSC Horizontal/Straight splicing closures are excellent protector of fibre optic joints from outdoor environment such as UV, water and weather with leak proof sealing. For easy splicing operation, closure consists of well managed no. of cable through and splice tray.



SCOPE OF APPLICATION

Aerial
Underground
Pipeline
Handhole

FEATURES

Made of high strength Polycarbonate.
Perfect Leak Proof with reliable sealing.
2-3 cable through each side for easy installation.
Suitable for Bunchy & Ribbon Fibre.

Characteristics	FOSCH1	FOSCH2
Dimension L x W x H	450 x 216 x 110	450 x 216 x 160
Weight	2750-3200g	3100-3800g
No. of Inlet:Outlet	3:3	
Cable Diameter	8.0-23.0mm	
Degree of Protection	IP65	
Ambient Temperature Range	-40°C to 65°C	
Max. Splice	Bunchy : 96 Core Ribbon : 216 Core	Bunchy : 192 Core Ribbon : 216 Core

Part Number	Description	No. Of Fibre Splice
325-H1012	12 Core Horizontal Splice Closure H1	12
325-H1024	24 Core Horizontal Splice Closure H1	24
325-H1048	48 Core Horizontal Splice Closure H1	48
325-H1072	72 Core Horizontal Splice Closure H1	72
325-H1096	96 Core Horizontal Splice Closure H1	96
325-H2048	48 Core Horizontal Splice Closure H2	48
325-H2096	96 Core Horizontal Splice Closure H2	96
325-H2144	144 Core Horizontal Splice Closure H2	144
325-H2192	192 Core Horizontal Splice Closure H2	192